



# HSM V-Press 860 TimeSave

## HSM V-Press 860 TimeSave vertical baling press

In addition to the well-known advantages of the V-Press series, the HSM V-Press 860 TimeSave has a decisive added-value factor: significant savings in time with less staff needed for the task. Thanks to the time-saving lifting/tilting device, it only takes a few seconds to load the HSM V-Press 860 TimeSave using a collection cart.

### Technical data

<b>Order number:</b>	6155304A	<b>Bale weight:</b>	430 kg
<b>EAN</b>	4026631075343	<b>Method of loading:</b>	Automatic lifting/tilting system, wire mesh cart
<b>Pressing power:</b>	594 kN	<b>Width x Depth x Height:</b>	2202 x 3584 x 3004 mm
<b>Specific pressing power:</b>	63,46 N/cm <sup>2</sup>	<b>Weight:</b>	3680 kg
<b>Driving power:</b>	7,0 kW (4+3 kW)	<b>Related product line:</b>	V-Press
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Type of consumables:</b>	Quick link wire
<b>Volume throughput in idle operation (theor.):</b>	26,25 m <sup>3</sup> /h	<b>Press material:</b>	Mixed paper, Cardboard
<b>Bale length x Bale width x Bale height:</b>	1200 x 1200 x 780 mm		

### Product information



Saves up to 1.5 h per bale compared to other vertical baling presses with automatic loading. Each cart is emptied within 12 seconds



Saves up to 5.0 h per bale compared to other vertical baling presses with manual loading



Convenient and particularly fast loading via hydraulic lifting/tilting device



### Economical

Optimised bale dimensions and bale weights for efficient storage, transport and direct commercialisation.



### Automatic start

Automatic start of the pressing process after closing the door.



### Economical, fast and silent

The HSM V-Presses are highly energy efficient thanks to the specially developed rapid stroke technology. This saves time and money.



### Graphic-capable display

Convenient membrane keypad with text display, which shows the current status of the machine.



### HSM TCS

HSM TCS (TorsionControlSystem) for monitoring press ram movement.



### Strapping

Manual bale strapping with Quick-link wire.



[www.tuev-sued.de/ps-zert](http://www.tuev-sued.de/ps-zert)

[www.hsm.eu](http://www.hsm.eu)

**HSM**®